



DECLARATION OF PERFORMANCE

No. WPSIT0055

1 – Unique identification code of the product-type:

WPSIT0055

2 - Identification of the construction product as required pursuant to Article 11(4) of Regulation (EU) No. 305/2011:

- FLAGON SRF
- FLAGON SRF Energy Plus (white version)
- 3 Intended use or uses of the construction product:

PVC membrane for waterproofing of roofings (EN 13956:2012)

4 – Name, registered trade name or registered trade mark and contact address of the manufacturer as required pursuant to Article 11(5) of Regulation (EU) No. 305/2011:

FLAG S.P.A Via Industriale dell'Isola, 3 24040 CHIGNOLO D'ISOLA (BG) www.soprema.it – www.flag-on.com

FLAG S.P.A. Via Selvapiana, 1 03020 VILLA SANTO STEFANO (FR) www.soprema.it - www.flag-on.com

5 – Name and contact address of the authorised representative whose mandate covers the tasks specified in Article 12(2) of Regulation (EU) No. 305/2011:

Not applicable

6 – System or systems of assessment and verification of constancy of performance of the construction product as set out in Annex V of Regulation (UE) No. 305/2011:

SYSTEM 2+

7 – Case of the declaration of performance concerning a construction product covered by a harmonised standard:

The ofi CERT (Notified Body No. 1085): - has performed the verification of the system of factory production control according to the system 2+ - has issued the certificate of conformity of the factory production control no. 1085-CPR-0010 for Chignolo and no.1085-CPR-0018 for Villa SS.

8 – Case of the declaration of performance concerning a construction product for which a European Technical Assessment has been issued:

Not applicable



DECLARATION OF PERFORMANCE

No. WPSIT0055

9 – Declared performance:

Essential characteristics	Performance	Test method	Harmonised technical specification
External fire performance	F ROOF	EN 13501-5	-
Reaction to fire	E	EN ISO 11925-2 EN 13501-1	
Watertightness	Pass	EN 1928 met. B	
Tensile properties:			
- Tensile strength (N/5cm)	≥ 1100	EN 12311-2 met.A	
- Elongation (%)	≥ 15	EN 12311-2 met.A	
Resistance to impact (mm)			
thickness 1,2 mm	≥ 450		
thickness 1,5 mm	≥ 800	EN 12691 met. A	
thickness 1,8 mm	≥ 900		EN 13956:2012
thickness 2,0 mm	≥ 1250		
Resistance to static loading (kg)	≥ 20	EN 12730	
Tear resistance (N)	≥ 200	EN 12310-2	
Joint strength:			
- Peel resistance (N/50mm)	≥ 200	EN 12316-2	
- Shear resistance (N/5cm)	> 600	EN 12317-2	
	break out joint		-
Foldability at low temperature	≤ -25°C	EN 495-5	
Resistance to root	resistant	EN 13948	
Durability:			
Exposure to UV radiation, elevated temperature and water	grade 0	EN 1297	
Dangerous substances	conforms	-	

10 – The performance of the product identified in points 1 and 2 is in conformity with the declared performance in point 9.

This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 4.

Signed for and on behalf of the manufacturer by:

Chignolo d'Isola, 10 April 2014 Managing Director, Mr. BROCCANELLO Bruno Flag S.p.A.

